

SUBMITTAL DATA SHEET



Series Name: 4-Way Cassette Hyper Heat Series
 Model Number: CCOXHBSZ36CHP/CCOXHB4C36
 Grille: CCOXHB4CP2448

4-Way Cassette Heat Pump System

Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:



INDOOR SPECIFICATION

Indoor Air Flow (Turbo/H/M/L/Si) (CFM)	1041.8 / 947.6 / 853.5 / 753.4 / 659.2
Indoor Noise Level (Turbo/H/M/L/Si) (dBA)	52/52/47.5/40/38
Dimension W×D×H (inches)	32.68 x 32.68 x 9.65
Package W×D×H (inches)	35.83 x 35.83 x 11.42
Net/Gross Weight lbs.	59.30/71.43

OUTDOOR SPECIFICATION

Compressor Type	TWIN-ROTARY
Compressor Model	EKPQ420D1UMUA
Refrigerant	R454B
Refrigerant Oil Charge(mL)	1460ml
Refrigerant Oil	3265
Outdoor Air Flow (Max) (CFM)	3001.9
Outdoor Noise Level (dBA)	64.5
Dimension W×D×H (inches)	38.58 x 16.34 x 38.39
Package W×D×H (inches)	45.08 x 19.68 x 42.52
Net/Gross Weight lbs.	206.57/237.44

EFFICIENCY

Cooling		Heating	
SEER2	21.2	HSPF2-4	10.6
EER2	12.0	COP	3.43

COOLING PERFORMANCE (Btu/hr)

Rated Capacity	36600
Min/Max Capacity	4900~38000
Moisture Removal(L/h)	4.30
Standard Operating Range(°F/°C)	-22~122(-30~50)
Conditions:	Indoor: 80°F DB/67°F WB Outdoor: 95°F DB/75°F WB

HEATING PERFORMANCE (Btu/hr)

1. @ 47°F Rated	37000
1. @ 47°F Min/Max Capacity	11400~44600
2. @ 17°F Rated	30600
3. @ 5°F Rated: Capacity / COP	37000/1.95
3. @ 5°F Max: Capacity	37000
Standard Operating Range(°F/°C)	-22~75(-30~24)
1. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 47°F DB/43°F WB
2. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 17°F DB/15°F WB
3. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 5°F DB/5°F WB


ELECTRICAL

Power Supply	208/230V,60Hz,1Ph
System MCA	38.00
Connection Wiring	14#x3
System MOCP	40
Compressor RLA	24.5
Outdoor Fan Motor RLA	2.1
Outdoor Fan Motor W	250
Indoor Fan Motor RLA	1.0
Indoor Fan Motor W	125
System Power Input @ Cooling (W)	3042(580 ~ 3480)
System Power Input @ Heating (W)	3161(740 ~4160)
MCA: Min. circuit amps (A)	MOCP: Max. over current protection (A)
RLA: Rated load amps (A)	W: Fan motor rated output (W)


PIPING

Throttle type(Indoor)	N/A
Throttle type(Outdoor)	EXV+Throttle valve
Liquid Size	9.52mm(3/8in)
Gas Size	19mm(3/4in)
Max. Piping Length(ft/m)	246.00(75)
Max. Height Difference(ft/m)	98.40(30)
Max. Pre-charged Length(ft/m)	24.6(7.5)
Refrigerant Pre-charged Amount(oz/kg)	126.99(3.60)
Additional Charge of Refrigerant((oz/ft)/(g/m)	0.32(30)
Connection Method	Flared

Indoor Unit Dimensions




Indoor Unit Clearances




Distance from ceiling relative to height of indoor unit

MODEL	Length of A	Length of H	Length of B
9K/12K/18K	9.6in (245mm)	>10.8in (275mm)	23.6in (600mm)
24K	8.03in (205mm)	9.06in (230mm)	35.4in (900mm)
36K	9.65in (245mm)	10.7in (271mm)	
48K	11.3in (287mm)	12.3in (313mm)	

Outdoor Unit Dimensions



Indoor Unit Clearances



Meets all spatial requirements shown in Installation Clearance Requirements above.

Features

- 360° Air Flow
- Remote on-off and alarm ports
- Refrigerant leakage detection sensor(Optional)
- Humidity sensor
- Built-in pump
- 1~100% fan speed setting
- WiFi capability: through WiFi dongle or wired controller with built-in WiFi
- OTA(by using WiFi dongle)
- 2-pin connector(HA/HB) for programmable wired controller
- Multiple control options available:
 - Two way communication wired controller:120N(X6)
 - Two way communication wired controller with built-in WiFi:120N(X6W)
 - Infrared wired controller: 120L
 - Wireless remote controller
 - Third-Party 24V Thermostat*

*24V interface is required.