

# SUBMITTAL DATA SHEET



Series Name: Hyper Heat AHU Series  
Model Number: CCOXHBSZ48CHP/CCOXHBAHUC48

## Air Handler Heat Pump System

Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:



## INDOOR SPECIFICATION

Indoor Air Flow (Turbo/H/M/L/Si) (CFM)	601.0 / 1471.5 / 1283.1 / 1094.8 / 1094.8
Indoor Noise Level (Turbo/H/M/L/Si) (dBA)	56.5/54.5/51/48/48
Dimensions WxDxH (inches)	24.49 x 21.02 x 52.99
Package WxDxH (inches)	27.95 x 26.77 x 56.50
Net/Gross Weight lbs.	161.82/191.58

## OUTDOOR SPECIFICATION

Compressor Type	TWIN-ROTARY
Compressor Model	EKPQ420D1UMUA
Refrigerant	R454B
Refrigerant Oil Charge(mL)	1460
Refrigerant Oil	VG75
Outdoor Air Flow (Max) (CFM)	4237.9
Outdoor Noise Level (dBA)	65
Dimensions WxDxH (inches)	37.48 x 16.34 x 52.48
Package WxDxH (inches)	43.11 x 19.49 x 57.48
Net/Gross Weight lbs.	208.78/239.86

## EFFICIENCY

Cooling		Heating	
SEER2	17	HSPF2-4	10.2
EER2	10	COP	3.5

## COOLING PERFORMANCE (Btu/hr)

Rated Capacity	48000
Min/Max Capacity	7300~55500
Moisture Removal(L/h)	4.84
Standard Operating Range(°F/°C)	-22~122(-30~50)
Conditions:	Indoor: 80°F DB/67°F WB Outdoor: 95°F DB/75°F WB

## HEATING PERFORMANCE (Btu/hr)

1. @ 47°F Rated	50000
1. @ 47°F Min/Max Capacity	9500~65000
2. @ 17°F Rated	40000
3. @ 5°F Rated: Capacity / COP	46000/2
3. @ 5°F Max: Capacity	46000
Standard Operating Range(°F/°C)	-22~75(-30~24)
1. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 47°F DB/43°F WB
2. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 17°F DB/15°F WB
3. Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 5°F DB/5°F WB


## ELECTRICAL

Power Supply	208/230V,60Hz,1Ph
System MCA	44
Communication Wiring	14#x3
System MOCP	45
Compressor RLA	27
Outdoor Fan Motor RLA	1.2
Outdoor Fan Motor W	85
Indoor Fan Motor RLA	7.8
Indoor Fan Motor W	750
System Power Input @ Cooling (W)	4752(1360 ~ 6250)
System Power Input @ Heating (W)	4186(720 ~ 5450)
MCA: Min. circuit amps (A)	MOCP: Max. over current protection (A)
RLA: Rated load amps (A)	W: Fan motor rated output (W)

## PIPING


Throttle type(Indoor)	N/A
Throttle type(Outdoor)	EXV+Throttle valve
Liquid Size	9.52mm(3/8in)
Gas Size	19mm(3/4in)
Max. Piping Length(ft/m)	246(75)
Max. Height Difference(ft/m)	98.4(30)
Max. Pre-charged Length(ft/m)	24.6(7.5)
Refrigerant Pre-charged Amount(oz/kg)	126.99(3.6)
Additional Charge (oz/ft)/(g/m)	0.32(30)
Connection Method	Flared

## Indoor Unit Dimensions




Dimensions	Model	18k/24k		30k/36k		48k/60k	
		inch	mm	inch	mm	inch	mm
A	Model Height	45	1143	49	1245	53	1346
B	Model Width	17-1/2	445	21	534	24-1/2	622
C	Supply Air Opening Width	15-5/8	397	19-1/8	486	22-5/8	575
D	Return Air Opening Width	15-1/8	384	18-5/8	473	22-1/8	562
E	Model Depth	21	534	21	534	21	534
F	Supply Air Opening Depth	10-1/4	260	10-1/4	260	10-1/4	260
G	Return Air Opening Depth	18-3/4	476	18-3/4	476	18-3/4	476
H	Supply Air Opening Clearance	15/16	24	15/16	24	15/16	24
I	Return Air Opening Side Clearance	1-1/4	32	1-1/4	32	1-1/8	28
J	Return Air Opening Front Clearance	1-1/2	38	1-5/8	41	1-5/8	41
K	Return Air Opening Back Clearance	5/8	16	5/8	16	3/4	19


### Outdoor Unit Dimensions



### Outdoor Unit Clearances



## Fan Performance For Indoor Unit



### Features

- Multi-position installation: horizontal(left or right), vertical( up or down)
- Aluminum Coil
- Constantly Air Flow system up to 0.80 In.W.G
- 1 inch R4.2 fiberglass free insulation reduces condensation and boosts efficiency(optional)
- Optional Auxiliary heat kit up to 25kW
- Easy Maintenance
- Multiple control options available:
  - Two way communication wired controller:120N(X6)
  - Two way communication wired controller with built-in WiFi:120N(X6W)
  - Wireless remote controller
  - Third-Party 24V Thermostat
- Chassis heater and crankcase heater equipped as standard

